

THINNER 3

PRODUCT CHARACTERISTICS

Description

THINNER 3 is universal Epoxy thinner for Epoxy product.

Recommended use

This product is used as all Epoxy Grade paint thinner to increase the flow and leveling of Epoxy Grade product.

Colors

Clear

Product Data

Parameters	Values
Solid Volume	0 %
Flash point	25 °C [77°F]
Density	0.85kg / l

SUBSTRATE & SURFACE PREPARATIONS

Mixed solvents

HEALTH AND SAFETY

Safety

Read and follow all caution statements on this product datasheet and on the MSDS for this product. Employ normal workman like safety precautions. Use adequate ventilation and wear gloves; or use protective cream on face and hands if hypersensitive. Keep the container closed when not in use.

Ventilation

When used in enclosed areas, thorough air circulation must be used during and after application until the coating is cured. The ventilation system should be capable of preventing the solvent vapor concentration from reaching the lower explosion limit for the solvents used. User should test and monitor the exposure levels to ensure all personnel are below guidelines. If not sure or if not able to monitor the levels, use an OSHA/NIOSH approved respirator.

Caution

This product contains flammable solvents. Keep away from sparks and open flames. In confined areas, workmen must wear the appropriate respirator protection. All electrical equipment and installations should be made and grounded in accordance with the National Electric Code. In areas where explosion hazards exist, workmen should be required to use nonferrous tools and wear conductive and non-sparking shoes.

PACKAGING, HANDLING AND STORAGE

Shipping Weight (Approximate)

5 Liters (4.25 Kg)

20 Liters (17 Kg)

THINNER 3

Handling

Handle with care. Before and during use, observe safety labels on packaging and paint containers and follow all local and national safety regulations. Always consult Pacific Paint's Safety Data Sheet for this product along with the Product Data Sheet.

Storage Temperature & Humidity

Temperature : 40 - 110°F(4-43°C)
Humidity : 0 - 100%

Shelf Life

48 months minimum at 23°C (actual stated shelf life) when kept at recommended storage conditions and in original unopened containers

WARRANTY

To the best of our knowledge the technical data contained herein is true and accurate on the date of publication and is subject to change without prior notice. User must contact Pacific Paint Factory to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We guarantee our products to conform to Pacific Paint Factory quality control. We assume no responsibility for coverage, performance, injuries or damages resulting from use. Pacific Paint Factory sole obligation, if any, is to replace or refund the purchase price of the Pacific Paint product(s) proven to be defective, at Pacific Paint Factory option. Pacific Paint Factory shall not be liable for any loss or damage.

NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY PACIFIC PAINT FACTORY, EXPRESS OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.
