

Description

THINNER 2 is universal thinner for range of Marine Master alkyd, acrylic, and antifouling type. Designed to improve the flow and used as cleaner for pumps and tools before and after painting.

Key Features

- Improve flow
- Cleaning solvent

Recommended Use

Recommended usage as per technical datasheet for the specific product to be applied.

Product Data

Properties

Type	: Thinner
Solid Volume	: 0%
Specific gravity	: 0.86 kg/l (calculated)
Flash point	: 25°C

Packaging Size

5 Liter
20 Liter

Application Data

Mixing

Single pack.

Storage Condition

Keep away from heat, fire and direct sunlight. Close the container tightly when not in use, keep in dry and cool room. Keep in temperature room (25-30 degree C).

Shelf-Life Product

Standard shelf life is 48 months from the date of manufacturing in originally not opened boxes, but may be extended based upon retesting by Pacific Paint Quality Control.

Health, Safety and Environment

Always use personal protective equipment and apply in a well-ventilated space. Caution with hazard symbol, see on packaging or refer to safety data sheet.

Read all safety, security, health and environment precautions before use. Wash hands and exposed skin before meals and after use. In case of contact with eyes and skin, rinse immediately with clean water, if swallowed or for more serious cases seek medical attention immediately.